

P2.97 MM

**INDOOR NOVASTAR**


Front Service / Back Service / Wall Mount

- Turn-key solution.
- Easy installation.
- Ground support compatible.
- Technical support available.
- 3 years warranty included for all parts.
- USA based.
- In stock. Ships immediately.



BACK

FRONT



**TECHNICAL SPECIFICATIONS**

PIXEL PITCH	P2.97 mm
LED ENCAPSULATION	King-Light SMD2020
PIXEL DENSITY	168 x 168
SIZE	500 x 500 x 75mm / 19.7" x 19.7" x 3"
CHIP	IC2153
HIGH REFRESH RATE	3840hz
WEIGHT	16 lbs./ 8 Kg
RECEIVING CARD	NovaStar


## POWER SUPPLY

OPERATION POWER	100~240V 50-60Hz
MAX. POWER CONSUMPTION	100W/per panel
AVE. POWER CONSUMPTION	50W/per panel
CONNECTIONS POWER/DATA	Power-PowerCon In/Out; Data EtherCon In/Out


## OPTICAL RATINGS

BRIGHTNESS	1500 NITS
PROTECTION RATE	IP45
SCAN	1/16
FRAME FREQUENCY	60 Hz
VIEW ANGLE	Horizontal 140°/Vertical 140°
OPTIMAL VIEW DISTANCE	6 ft (2m)
BRIGHTNESS ADJUSTMENT	0~100% 100 Levels

### FRONT SIZES



### SIDE SIZES



## VIEWING DISTANCE

8	Pixel Pitch (mm)	5.9	3.9	2.9	1.9	1.5	1.2	0.9
26 ft.	Optimal Viewing Distance	20 ft.	8 ft.	6 ft.	5 ft.	4 ft.	3 ft.	2 ft.

